Ultra-Super



Butt end sewing machine on rail for heavy to heaviest fabrics and materials





Ultra-Super



Sewing unit

The robust sewing unit is suitable for dry and for wet fabrics. Cutting and sewing take place in one single step. The two fabric ends are joined by the sewing thread. After unfolding the two ends the connection is flat and broad (appr. 50mm).

Cutting device

The powerful cutting device is equipped with an HSS-cutter driven by a separate motor. The counter-knife is made of extreme durable carbid metal. The special shape of the cutting device allows the cut material to pass easily, even stiff materials can be cut.

The step by step motion

As long as the eyed needle is inside the fabric the forward motion of the machine nearly stops. This special feature significantly reduces needle deflection.

As a result, stiff and hard fabrics and materials can be sewn.








Universal and robust

The broad seams of the Ultra-Super are strong and tear resistant. Thick or thin materials, soft or hard: the Ultra-Super copes with sewing tasks which are not possible for standard sewing machines.





Ultra-Super



Seam type:

Single-thread butt to butt seam

Seam width:

appr. 50mm (Option 60mm)

Sewing length:

as desired, e.g. 1,600 mm; 2,200 mm; 3,600 mm; 5,400 mm, etc.

Voltage:

400V, 50 HZ, three-phase; other voltages possible

Cutting device:

HSS-knife diameter 200mm Counter-knife carbid metal Cutting device axially adjustable for:

- butt to butt (flat) or
- -gap or
- overlap

Fixation of the fabric:

Right and left clamping holders, combined with intermediate holders

Optionen:

Supporting table (stainless steel), hinged bar for fixation of the material

Technical changes reserved (Dec. 2013) More options and special designs available, give us a call or send us samples.



Dohle machines. In use worldwide.



Dohle GmbH & Co. KG Zechenstr. 130 52249 Eschweiler, GERMANY

Tel.: +49 (0) 2403 233 71 Fax: +49 (0) 2403 24 897

www.dohle.de info@dohle.de

